

## **COSHH Assessment Record**



Product Name (Ref.)	WD-40							
Description of how product is used	Anti-squeak. Moisture repellent. Releasing agent.							
Health Risk / Hazard Identification	R10 - Flammable R65 - Harmful : may cause lung damage if swallowed R66 - Repeated exposure may cause skin dryness or cracking							
Hazardous Content/Ingredient	Carbon Dioxide Petroleum Distillate							
Routes of Exposure	Skin ☑ Eyes ☑ Inhalation ☑ Swallowing ☑ Cuts □							
Maximum Exposure Limit (MEL)	Not Known							
Occupational Exposure Limit (OEL)	Not Known							
Product Risk	High □	Medium ☑	Low					
Can this product be substituted?	Not Required							
Safety Controls required	S2 - Keep out of reach of children S16 - Keep away from sources of ignition S23 - Do not breathe vapour/spray S37 - Wear suitable gloves S51 - Use only in well-ventilated areas							
Personal Protective Equipment (PPE) requirements	Chemical resistant gloves to be worn if there is a risk of skin contact.  Wear eye protection if there is a risk of accidental eye contact.							
First Aid Requirements: Inhalation Ingestion Skin Eye contact	Remove to fresh air, keep warm and at rest.  Do not induce vomiting and drink plenty of water.  Wash off immediately with plenty of soap and water  Rinse thoroughly with plenty of water for 15 minutes.  In all cases seek medical advice if irritation persists							
Fire Fighting Measures	Use Foam, Water Spray, Dry Chemicals, Sand, Dolmite etc							
Handling and Storage	Keep away from heat, sparks and open flame. Wash hands after use. Do not expose to direct sunlight or temperatures above 50°C							
Accidental Spillage	Absorb with inert, damp, non-combustible material then flush area with water.							
Overall Product Risk (taking into account all information and control measurers)	High □ Medium □ Low ☑							
Originally Completed By	Simon Dean							
Reviewed By	Lawrence Large	Date	24 May 2011					

At all times refer to Safety Data Sheets for specific specifications



## **COSHH Assessment Record**



Product Name (Ref.)	Arecal Long Lube								
Description of how product is used	Lubricant								
Health Risk / Hazard Identification	R12 - Extremely Flammable								
Hazardous Content/Ingredient	Iso-Butane Propane/Butane								
Routes of Exposure	Skin ☑	Eyes ☑	Inhala	tion ☑	Swall	owing 🗆	Cı	uts 🗆	
Maximum Exposure Limit (MEL)	Iso-Butan Propane/B			750ppm 750ppm					
Occupational Exposure Limit (OEL)	Iso-Butan Propane/E			600ppm 600ppm					
Product Risk	Higl	h 🗆		Medium			Low		
Can this product be substituted?	Not Required								
Safety Controls required	S23/4: DO not breathe spray S51: Use only in well ventilated areas								
Personal Protective Equipment (PPE) requirements	Breathing apparatus in the event of high concentrations. Short term: filter apparatus, Filter A. Suitable protective gloves: Butyl rubber, >480 min (EN374)								
First Aid Requirements: Inhalation Ingestion Skin Eye contact	Remove to fresh air No action required Wash off immediately with plenty of soap and water Rinse thoroughly with plenty of water In all cases seek medical advice if irritation persists								
Fire Fighting Measures	All extinguishing substances suitable. Do not use a full water jet.								
Handling and Storage	Use only in well ventilated areas. Do not store together with oxidizing agents. Store at room temperature								
Accidental Spillage	Use of a cloth and or mop and bucket.								
Overall Product Risk (taking into account all information and control measurers)	Hig	h 🗆		Medium			Low	Ø	
Originally Completed By	Simon Dea	an							
Reviewed by	Lawrence	Large		Date		24 May	2011		

At all times refer to Safety Data Sheets for specific specifications